

Utility Range

UC5/A– Mid Back

- 1) Mechanism
 - Swivel & tilt mechanism with back tension adjustment
 - Right hand controls
 - Height adjustment lever
- 2) Gas Spindle
 - Executive single taper – Class 4
- 3) Base
 - 600mm Nylon base with 50mm hooded castors
 - Option of Chrome base
- 4) Sub Frame
 - 22.23mm Square tubing - Cold rolled steel with 1.2mm wall thickness
 - Option of chrome, silver or white powder coated frame
- 5) Seat
 - 16mm Chipboard
 - VP70 high density foam
- 6) Back
 - Pressed plywood
 - VP30 medium density foam
- 7) Arms rest – Standard on UC5A
 - Plastic arms fitted to frame



UC3 – Arm Chair

- Same features for seat and back
- 4 Legged, 22.23mm Square tubing frame - Cold rolled steel with 1.2mm wall thickness
- Option of chrome, silver or white powder coated frame
- Plastic arms fitted to frame

UC2 – Side chair

- Same features for seat and back
- 4 Legged, 22.23mm Square tubing frame - Cold rolled steel with 1.2mm wall thickness
- Option of chrome, silver or white powder coated frame



Utility Range

Dimensions		UC5A	UC5	UC3	UC2
Local Content 		≥ 94%	≥ 94%	100%	100%
Overall Height		820 mm	820 mm	830 mm	830 mm
Overall Width		560 mm	560 mm	560 mm	540 mm
Overall Depth		630 mm	630 mm	570 mm	570 mm
Total Weight		13 kg	12 kg	8 kg	7 kg
Seat Height	Lowest	470 mm	470 mm	480 mm	480 mm
	Highest	560 mm	560 mm		

