

Scoop Range

NPUB1 – Industrial PU Stool

- 1) Mechanism
 - Swivel plate
 - Hand control
 - Height adjustment lever
- 2) Gas Spindle
 - Typist gas – Class 4
- 3) Base
 - 600mm Nylon base with 50mm hooded castors
 - Option of Chrome base
- 4) Seat
 - Solid polyurethane moulded onto a 3mm base plate and 6mm round bar outer support



NPUB9 – Industrial PU Draughtsman Stool

- 1) Mechanism
 - Swivel plate
 - Hand control
 - Height adjustment lever
- 2) Gas Spindle
 - Draughtsman – Class 4
- 3) Base
 - 700mm Nylon base with 50mm hooded castors
 - Option of Chrome base
- 4) Foot ring
 - 25mm Round tubing – Cold rolled steel with 1.2mm wall thickness
 - 10mm Mild steel struts
 - Option of chrome, nylon or free-standing foot ring
- 5) Seat
 - Solid polyurethane moulded onto a 3mm base plate and 6mm round bar outer support



FSFR/C – Free standing foot ring

- Ring 500Ø - 25mm Round tubing – Cold rolled steel with 1.2mm wall thickness
- Legs - 22.23mm Square tubing – Cold rolled steel with 1.2mm wall thickness
 - Levelling adjusters
 - Option of black powder coated or chromed
 - Option of 400Ø or 500Ø ring



Scoop Range

Dimensions		NPUB1	NPUB9	NPUB9 FSFR
Local Content 		100%	100%	100%
Overall Height		550 mm	730 mm	780 mm
Overall Width		485 mm	485 mm	520 mm
Overall Depth		470 mm	485 mm	520 mm
Total Weight		6 kg	8.5 kg	9 kg
Seat Height	Lowest	440 mm	620 mm	670 mm
	Highest	570 mm	870 mm	920 mm

